

according to UK REACH Regulation

# MIT700RE, Comp. A

Revision date: 29.11.2022

Page 1 of 12

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

MIT700RE, Comp. A

UFI:

GV8S-7W26-0408-M7J7

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Adhesive mortar for fastening elements A-component (resin)

#### Uses advised against

no restriction

#### 1.3. Details of the supplier of the safety data sheet

Company name:	Mungo Befestigungstechnik AG	6
Street:	Bornfeldstraße 2	
Place:	CH-4600 Olten	
Telephone: e-mail: Internet:	+41 62 2067575 mungo@mungo.swiss www.mungo.swiss	Telefax:+41 62 2067585
<u>1.4. Emergency telephone</u> number:	+49 (0)551-19240 (GIZ-Nord, G	German and English, 24/7)

## **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

#### **GB CLP Regulation**

Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

## 2.2. Label elements

#### **GB CLP Regulation**

#### Hazard components for labelling

2,2'-[(1-Methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane;

1,6-hexanediol diglycidyl ether Warning

Signal word:

## **Pictograms:**



## Hazard statements

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H411	Toxic to aquatic life with long lasting effects.

#### **Precautionary statements**

P264	Wash hands thoroughly after handling.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.



## according to UK REACH Regulation

## MIT700RE, Comp. A

	Revision date: 29.11.2022	
--	---------------------------	--

Page 2 of 12

P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P391	Collect spillage.

## 2.3. Other hazards

People who are allergic to epoxide should avoid the use of the product. Use only outdoors or in a well-ventilated area.

#### **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

#### Hazardous components

CAS No	Chemical name			Quantity	
	EC No	Index No	REACH No		
	Classification (GB CLP Regulat	ion)			
1675-54-3	2,2'-[(1-Methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane			30 - < 60 %	
	216-823-5	603-073-00-2 01-2119456619-26			
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H319 H317 H411				
933999-84-9	1,6-hexanediol diglycidyl ether			10 - < 15 %	
	618-939-5	01-2119463471-41			
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 3; H315 H319 H317 H412				

#### Full text of H and EUH statements: see section 16.

#### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity	
	Specific Conc.	Limits, M-factors and ATE		
1675-54-3	216-823-5	2,2'-[(1-Methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	30 - < 60 %	
	dermal: LD50 = 23000 mg/kg; oral: LD50 = 15000 mg/kg Skin Irrit. 2; H315: >= 5 - 100 Eye Irrit. 2; H319: >= 5 - 100			
933999-84-9	618-939-5	1,6-hexanediol diglycidyl ether	10 - < 15 %	
	dermal: LD50 = > 2000 mg/kg; oral: LD50 = 3010 mg/kg			

## **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### **General information**

First aider: Pay attention to self-protection! Take off immediately all contaminated clothing and wash it before reuse. Get medical advice/attention if you feel unwell.

#### After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

#### After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

#### After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing.

#### After ingestion

Do NOT induce vomiting. Rinse mouth thoroughly with water. Medical treatment necessary.

#### 4.2. Most important symptoms and effects, both acute and delayed

#### Causes skin irritation. May cause an allergic skin reaction.

Causes serious eye irritation.



according to UK REACH Regulation

## MIT700RE, Comp. A

Page 3 of 12

## Revision date: 29.11.2022

#### **4.3. Indication of any immediate medical attention and special treatment needed** Treat symptomatically.

## **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

#### Suitable extinguishing media

Foam Extinguishing powder Water spray jet Carbon dioxide (CO2)

#### Unsuitable extinguishing media

Full water jet

#### 5.2. Special hazards arising from the substance or mixture

Pyrolysis products, toxic Carbon monoxide

#### 5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit

#### **Additional information**

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Provide adequate ventilation.

#### 6.2. Environmental precautions

Avoid release to the environment. Do not allow to enter into surface water or drains.

#### 6.3. Methods and material for containment and cleaning up

#### Other information

Collect spillage. Take up mechanically, placing in appropriate containers for disposal. Suitable material for taking up: Sand

Treat the recovered material as prescribed in the section on waste disposal. Retain contaminated washing water and dispose it.

## 6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

## **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

#### Advice on safe handling

Use only outdoors or in a well-ventilated area. Wear personal protection equipment (refer to section 8). Avoid contact with skin, eyes and clothes. When using do not eat, drink or smoke.

#### Advice on general occupational hygiene

Take off contaminated clothing and wash it before reuse. Draw up and observe skin protection programme.



according to UK REACH Regulation

# MIT700RE, Comp. A

Revision date: 29.11.2022

Page 4 of 12

Wash hands thoroughly after handling. When using do not eat, drink or smoke.

## 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed. Store in a place accessible by authorized persons only. Keep only in the original container in a cool, well-ventilated place.

#### Hints on joint storage

Do not store together with: Oxidising agent, strong Do not use for products which come into contact with the food stuffs.

#### Further information on storage conditions

storage temperature: 5 - 35°C

#### 7.3. Specific end use(s)

Adhesive mortar for fastening elements A-component (resin)

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

#### **DNEL/DMEL values**

CAS No	Substance	_	_	_
DNEL type		Exposure route	Effect	Value
933999-84-9	1,6-hexanediol diglycidyl ether			
Worker DNEL	, long-term	inhalation	systemic	10,57 mg/m³
Worker DNEL	, long-term	inhalation	local	0,44 mg/m³
Worker DNEL	., long-term	dermal	systemic	6,0 mg/kg bw/day
Worker DNEL	., long-term	dermal	local	0,0226 mg/cm <sup>2</sup>
Consumer DN	IEL, long-term	inhalation	systemic	5,29 mg/m³
Consumer DN	IEL, long-term	inhalation	local	0,27 mg/m³
Consumer DN	IEL, long-term	dermal	systemic	3,0 mg/kg bw/day
Consumer DN	IEL, long-term	dermal	local	0,0136 mg/cm <sup>2</sup>
Consumer DN	IEL, acute	inhalation	systemic	5,29 mg/m³
Consumer DN	IEL, acute	dermal	systemic	1,7 mg/kg bw/day
Consumer DN	IEL, acute	dermal	local	0,0136 mg/cm <sup>2</sup>
Consumer DN	IEL, long-term	oral	systemic	1,5 mg/kg bw/day
Consumer DN	IEL, acute	oral	systemic	1,5 mg/kg bw/day

**PNEC** values

CAS No	Substance		
Environmenta	Environmental compartment Value		
933999-84-9	933999-84-9 1,6-hexanediol diglycidyl ether		
Freshwater		0,0115 mg/l	
Marine water		0,00115 mg/l	
Freshwater sediment		0,283 mg/kg	
Marine sediment		0,283 mg/kg	

#### Additional advice on limit values

This mixture contains quartz (inorganic filler) which is firmly bound in the pasty component, and thus not freely available during use, so that a risk of dust inhalation is excluded. Exposure limit values for respirable dusts are not relevant for this product.



according to UK REACH Regulation

# MIT700RE, Comp. A

Page 5 of 12

## Revision date: 29.11.2022

## 8.2. Exposure controls





## Appropriate engineering controls

Provide adequate ventilation. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means.

## Individual protection measures, such as personal protective equipment

#### **Eye/face protection**

Wear eye/face protection. Wear safety glasses.

#### Hand protection

Recommended material: NBR (Nitrile rubber) Breakthrough time: > 480 min Thickness of the glove material: 0,7 mm DIN-/EN-Norms EN 374

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

#### Skin protection

Wear suitable protective clothing.

#### **Respiratory protection**

In case of inadequate ventilation wear respiratory protection. Respiratory protection with combination filter A1P2 (organic gases/vapors and particles) recommended.

## **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Physical state: Colour:	solid (pasty) light beige	
Odour: Odour threshold:	characteristic No data available	
<b>Changes in the physical state</b> Melting point/freezing point: Boiling point or initial boiling point and boiling range: Flash point:		not determined not determined not applicable
Flammability Solid/liquid: Gas:		not determined not applicable
Explosive properties The product is not: Explosive.		
Lower explosion limits: Upper explosion limits:		not determined not determined
<b>Self-ignition temperature</b> Solid: Gas:		not determined not applicable
Decomposition temperature:		not determined



Revision date: 29.11.2022

# **Safety Data Sheet**

according to UK REACH Regulation

## MIT700RE, Comp. A

Page 6 of 12

pH-Value:	not determined		
Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.		
Solubility in other solvents not determined			
Partition coefficient n-octanol/water:	not determined		
Vapour pressure:	not determined		
Density (at 20 °C):	1,45 g/cm³		
Relative vapour density:	not determined		
9.2. Other information			
Information with regard to physical h Oxidizing properties Not oxidising.	nazard classes		
Other safety characteristics			
Solid content:	not determined		
Evaporation rate:	not determined		
SECTION 10: Stability and reactivity			

## 10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

## 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

## 10.3. Possibility of hazardous reactions

Violent reaction with: Oxidising agent, strong

#### 10.4. Conditions to avoid

Heat. Keep cool. Protect from sunlight.

## 10.5. Incompatible materials

Keep away from: Oxidizing agent

## 10.6. Hazardous decomposition products

No known hazardous decomposition products.

# **SECTION 11: Toxicological information**

# 11.1. Information on hazard classes as defined in GB CLP Regulation

## Acute toxicity

Based on available data, the classification criteria are not met.



Page 7 of 12

according to UK REACH Regulation

# MIT700RE, Comp. A

Revision date: 29.11.2022

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
1675-54-3	2,2'-[(1-Methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane					
	oral	LD50 mg/kg	15000	Rat		
	dermal	LD50 mg/kg	23000	Rabbit		
933999-84-9	1,6-hexanediol diglycid	yl ether				
	oral	LD50 mg/kg	3010	Rat		
	dermal	LD50 mg/kg	> 2000	Rat		OECD 402

## Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

## Sensitising effects

May cause an allergic skin reaction. (2,2'-[(1-Methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane; 1,6-hexanediol diglycidyl ether)

## Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

## STOT-single exposure

Based on available data, the classification criteria are not met.

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

#### **Further information**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

## **SECTION 12: Ecological information**

#### 12.1. Toxicity

Toxic to aquatic life with long lasting effects.

	-
CAS No	Chemi

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method
1675-54-3	2,2'-[(1-Methylethylidene	e)bis(4,1-pl	henyleneo	ymethy	lene)]bisoxirane		
	Acute fish toxicity	LC50	2 mg/l		Oncorhynchus mykiss (Rainbow trout)		
	Acute algae toxicity	ErC50	11 mg/l	72 h			
	Acute crustacea toxicity	EC50	1.8 mg/l		Daphnia magna (Big water flea)		
933999-84-9	1,6-hexanediol diglycidy	l ether					
	Acute fish toxicity	LC50	30 mg/l		Oncorhynchus mykiss (Rainbow trout)		
	Acute crustacea toxicity	EC50	47 mg/l		Daphnia magna (Big water flea)		

## 12.2. Persistence and degradability

The product has not been tested.



according to UK REACH Regulation

## MIT700RE, Comp. A

Revision date: 29.11.2022

Page 8 of 12

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
933999-84-9	1,6-hexanediol diglycidyl ether			
	OECD 301D	71 %	28	

#### 12.3. Bioaccumulative potential

The product has not been tested.

# Partition coefficient n-octanol/water CAS No Chemical name Log Pow 933999-84-9 1,6-hexanediol diglycidyl ether 0,822

201				
CAS No	Chemical name	BCF	Species	Source
933999-84-9	1,6-hexanediol diglycidyl ether	3,57		

#### 12.4. Mobility in soil

The product has not been tested.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH. The product has not been tested.

The product has not been tested.

## 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

## 12.7. Other adverse effects

No information available.

## **Further information**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

## **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

#### **Disposal recommendations**

Subsequent waste code numbers of the European Waste Catalogue are considered as recommendations. Dispose of waste according to applicable legislation. Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

#### List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

#### List of Wastes Code - used product

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

## List of Wastes Code - contaminated packaging



Revision date: 29.11.2022

according to UK REACH Regulation

# MIT700RE, Comp. A

Page 9 of 12

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

## **SECTION 14: Transport information**

Land transport (ADR/RID)	UN 3077
<u>14.1. UN number or ID number:</u>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
<u>14.2. UN proper shipping name:</u>	(Epoxy resin)
<u>14.3. Transport hazard class(es):</u>	9
<u>14.4. Packing group:</u>	III
Hazard label:	9
	M7 274 335 375 601 5 kg E1 3 90 - <b>ransport)</b> until 5 kg according special instruction 375 ADR/RID
Inland waterways transport (ADN)	UN 3077
<u>14.1. UN number or ID number:</u>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
<u>14.2. UN proper shipping name:</u>	(Epoxy resin)
<u>14.3. Transport hazard class(es):</u>	9
<u>14.4. Packing group:</u>	III
Hazard label:	9
Classification code:	M7
Special Provisions:	274 335 375 601
Limited quantity:	5 kg
Excepted quantity:	E1
<b>Other applicable information (inland</b>	I waterways transport)
No dangerous goods in packaging	until 5 kg according special instruction 375 ADN
Marine transport (IMDG)	UN 3077
<u>14.1. UN number or ID number:</u>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
<u>14.2. UN proper shipping name:</u>	(Epoxy resin)
<u>14.3. Transport hazard class(es):</u>	9
<u>14.4. Packing group:</u>	III
Hazard label:	9



# **Safety Data Sheet**

according to UK REACH Regulation

## MIT700RE, Comp. A

0 of 12

Revision date: 29.11.2022	Page 10
Special Provisions: Limited quantity: Excepted quantity: EmS: <b>Other applicable information (marine</b> No dangerous goods in packaging u	274, 335, 966, 967, 969 5 kg E1 F-A, S-F <b>e transport)</b> Intil 5kg according 2.10.2.7 IMDG Code
Air transport (ICAO-TI/IATA-DGR)	
14.1. UN number or ID number: 14.2. UN proper shipping name:	UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Epoxy resin)
<u>14.3. Transport hazard class(es):</u>	9
14.4. Packing group:	III
Hazard label:	9
Special Dravisiona:	A97 A158 A179 A197
Special Provisions: Limited quantity Passenger:	30 kg G
Passenger LQ:	Y956
Excepted quantity:	F1
IATA-packing instructions - Passenger:	
IATA-max. quantity - Passenger:	400 kg
IATA-packing instructions - Cargo:	956
IATA-max. quantity - Cargo:	400 kg
Other applicable information (air tran	
No dangerous goods in packaging u	until 5 kg according A197 IATA-DGA
14.5. Environmental hazards	
ENVIRONMENTALLY HAZARDOUS:	Yes
<b>14.6. Special precautions for user</b> No information available.	

14.7. Maritime transport in bulk according to IMO instruments

not applicable

## **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulatory information

Restrictions on use (REACH, annex XVII): Entry 75 Information according to 2012/18/EU E2 Hazardous to the Aquatic Environment (SEVESO III):

## Additional information

VOC content: < 0,1 % (DIN EN ISO 11890-2)

To follow: 850/2004/EC , 79/117/EEC , 689/2008/EC

## National regulatory information



according to UK REACH Regulation

# MIT700RE, Comp. A

Page 11 of 12

**Employment restrictions:** 

Water hazard class (D):

Revision date: 29.11.2022

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). 2 - obviously hazardous to water Causes allergic hypersensitivity reactions.

## 15.2. Chemical safety assessment

Skin resorption/Sensitization:

Chemical safety assessments for substances in this mixture were not carried out.

# **SECTION 16: Other information**

#### Abbreviations and acronyms

ADN: Accord européen relativ au transport international des marchandises Dangereuses par voie de Navigation

(European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways) ADR: Accord européen sur le transport des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road) BCF: Bioconcentration factor CAS: Chemical Abstracts Service CLP: Classification, Labeling and Packaging DMEL: Derived Minimal Effect level **DNEL: Derived No Effect Level** EC50: Effective concentration, 50% IATA: International Air Transport Association IATA-DGR: Dangerous Goods Regulations (DRG) for the air transport (IATA) ICAO: International Civil Aviation Organization IC50: Inhibitory concentration, 50% IMDG: International Maritime Code for Dangerous Goods LC50: Lethal concentration. 50% LD50: Lethal dose, 50% NOEC: No Observed Effect Concentration OECD: Oragnisation for Economic Co-operation and Development PBT: persistent, bioaccumulative and toxic vPvB: very persistent and very bioaccumulative PNEC: Predicted No Effect Concentration REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals RID: Règlement concernant le transport international ferroviaire de marchandises dangereuses (Regulations Concerning the International Carriage of Dangerous Goods by Rail) VOC: Volatile organic compound Aquatic Chronic 2: Long-term aquatic hazard, Category 2 Aquatic Chronic 3: Long-term aquatic hazard, Category 3 Eye Irrit. 2: Serious eye damage/eye irritation, Category 2 Skin Irrit. 2: Serious eye damage/eye irritation, Category 2

Skin Sens. 1: Skin sensitilization, Category 1

## Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method
Aquatic Chronic 2; H411	Calculation method

## Relevant H and EUH statements (number and full text)

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.



according to UK REACH Regulation

# MIT700RE, Comp. A

Revision date: 29.11.2022

Page 12 of 12

H412

Harmful to aquatic life with long lasting effects.

## **Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)



according to UK REACH Regulation

# MIT700RE, Comp. B

Revision date: 29.11.2022

Page 1 of 13

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

MIT700RE, Comp. B

UFI:

HY8S-QWRK-940R-8K49

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

compound mortar B-component (hardener)

#### Uses advised against

no restriction

#### 1.3. Details of the supplier of the safety data sheet

Company name:	Mungo Befestigungstechnik AG	
Street:	Bornfeldstraße 2	
Place:	CH-4600 Olten	
Telephone:	+41 62 2067575	Telefax:+41 62 2067585
e-mail:	mungo@mungo.swiss	
Internet:	www.mungo.swiss	
1.4. Emergency telephone	+49 (0)551-19240 (GIZ-Nord, Ge	erman and English, 24/7)
<u>number:</u>		

# **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

#### GB CLP Regulation

Acute Tox. 4; H302 Skin Corr. 1A; H314 Eye Dam. 1; H318 Skin Sens. 1; H317

Full text of hazard statements: see SECTION 16.

#### 2.2. Label elements

#### **GB CLP Regulation**

#### Hazard components for labelling

2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine; m-Phenylenebis(methylamine); 2,4,6-Tris(dimethylaminomethyl)phenol

Signal word: Danger

# Pictograms:



#### **Hazard statements**

H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.

#### **Precautionary statements**

ooddelollary oldloll	
P260	Do not breathe dusts or mists.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.



## according to UK REACH Regulation

## MIT700RE, Comp. B

Revision date: 29.11.2022	Page 2 of 13
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with
P333+P313	water or shower. If skin irritation or rash occurs: Get medical advice/attention

P333+P313If skin irritation or rash occurs: Get medical advice/attention.P501Dispose of contents/container to an approved waste disposal plant in accordance with<br/>local/national regulation.

#### 2.3. Other hazards

Contains Amines. May produce an allergic reaction. Use only outdoors or in a well-ventilated area.

## **SECTION 3: Composition/information on ingredients**

## 3.2. Mixtures

#### Hazardous components

Chemical name				
EC No	Index No	REACH No		
Classification (GB CLP Regulat	ion)	·		
2,2,4(or 2,4,4)-Trimethylhexane	-1,6-diamine		25 - < 35 %	
247-063-2		01-2119560598-25		
Acute Tox. 4, Skin Corr. 1A, Ey	e Dam. 1, Skin Sens. 1A; H302 I	H314 H318 H317		
m-Phenylenebis(methylamine)			1 - < 8 %	
216-032-5		01-2119480150-50		
Acute Tox. 4, Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Skin Sens. 1B, Aquatic Chronic 3; H332 H302 H314 H318 H317 H412				
2,4,6-Tris(dimethylaminomethyl)phenol				
202-013-9		01-2119560597-27		
Acute Tox. 4, Skin Corr. 1C, Eye Dam. 1; H302 H314 H318				
p-Toluenesulphonic acid			1 - < 5 %	
203-180-0	016-030-00-2	01-2119538811-39		
Skin Irrit. 2, Eye Irrit. 2, STOT SE 3; H315 H319 H335				
	EC No Classification (GB CLP Regulat 2,2,4(or 2,4,4)-Trimethylhexane 247-063-2 Acute Tox. 4, Skin Corr. 1A, Ey m-Phenylenebis(methylamine) 216-032-5 Acute Tox. 4, Acute Tox. 4, Skin H302 H314 H318 H317 H412 2,4,6-Tris(dimethylaminomethyl 202-013-9 Acute Tox. 4, Skin Corr. 1C, Ey p-Toluenesulphonic acid 203-180-0	EC NoIndex NoClassification (GB CLP Regulation)2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine247-063-2Acute Tox. 4, Skin Corr. 1A, Eye Dam. 1, Skin Sens. 1A; H302 Im-Phenylenebis(methylamine)216-032-5Acute Tox. 4, Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Skin SenH302 H314 H318 H317 H4122,4,6-Tris(dimethylaminomethyl)phenol202-013-9Acute Tox. 4, Skin Corr. 1C, Eye Dam. 1; H302 H314 H318p-Toluenesulphonic acid203-180-0016-030-00-2	EC No       Index No       REACH No         Classification (GB CLP Regulation)       2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine         247-063-2       01-2119560598-25         Acute Tox. 4, Skin Corr. 1A, Eye Dam. 1, Skin Sens. 1A; H302 H314 H318 H317       m-Phenylenebis(methylamine)         216-032-5       01-2119480150-50         Acute Tox. 4, Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Skin Sens. 1B, Aquatic Chronic 3; H332         H302 H314 H318 H317 H412         2,4,6-Tris(dimethylaminomethyl)phenol         202-013-9       01-2119560597-27         Acute Tox. 4, Skin Corr. 1C, Eye Dam. 1; H302 H314 H318         p-Toluenesulphonic acid       016-030-00-2         203-180-0       016-030-00-2       01-2119538811-39	

Full text of H and EUH statements: see section 16.

#### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Con	c. Limits, M-factors and ATE	
25513-64-8	247-063-2	2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine	25 - < 35 %
	oral: ATE = {	500 mg/kg	
1477-55-0	216-032-5	m-Phenylenebis(methylamine)	1 - < 8 %
		C50 = 3,89 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: mg/kg; oral: LD50 = 930 mg/kg	
90-72-2	202-013-9	2,4,6-Tris(dimethylaminomethyl)phenol	5 - < 10 %
	dermal: LD5	0 = 1280 mg/kg; oral: LD50 = 2169 mg/kg	
104-15-4	203-180-0	p-Toluenesulphonic acid	1 - < 5 %
	STOT SE 3;	H335: >= 20 - 100	

## **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

#### **General information**

First aider: Pay attention to self-protection! Remove affected person from the danger area and lay down. Take off immediately all contaminated clothing and wash it before reuse. Get medical advice/attention if you feel unwell.



according to UK REACH Regulation

## MIT700RE, Comp. B

Page 3 of 13

Revision date: 29.11.2022

## After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

#### After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

#### After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing.

#### After ingestion

Do NOT induce vomiting. Rinse mouth thoroughly with water. Medical treatment necessary.

#### 4.2. Most important symptoms and effects, both acute and delayed

#### Harmful if swallowed.

Causes severe skin burns and eye damage. May cause an allergic skin reaction.

## 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

#### Suitable extinguishing media

Foam Extinguishing powder Water spray jet Carbon dioxide (CO2)

#### Unsuitable extinguishing media

Full water jet

#### 5.2. Special hazards arising from the substance or mixture

Pyrolysis products, toxic Carbon monoxide

#### 5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Wear a self-contained breathing apparatus and chemical protective clothing.

#### Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

## **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

## General advice

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Provide adequate ventilation.

## 6.2. Environmental precautions

Avoid release to the environment. Do not allow to enter into surface water or drains.

## 6.3. Methods and material for containment and cleaning up

## Other information

Collect spillage. Take up mechanically, placing in appropriate containers for disposal. Suitable material for taking up: Sand

Treat the recovered material as prescribed in the section on waste disposal. Retain contaminated washing water and dispose it.



according to UK REACH Regulation

# MIT700RE, Comp. B

Page 4 of 13

Revision date: 29.11.2022

## 6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

## **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

#### Advice on safe handling

Use only outdoors or in a well-ventilated area. Wear personal protection equipment (refer to section 8). Avoid contact with skin, eyes and clothes. When using do not eat, drink or smoke.

#### Advice on general occupational hygiene

Take off contaminated clothing and wash it before reuse. Draw up and observe skin protection programme. Wash hands thoroughly after handling. When using do not eat, drink or smoke.

## 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed. Store in a place accessible by authorized persons only. Keep only in the original container in a cool, well-ventilated place.

## Hints on joint storage

Do not store together with: Oxidising agent, strong, Organic peroxides Do not use for products which come into contact with the food stuffs.

#### Further information on storage conditions

Keep container tightly closed in a cool place. storage temperature: 5 - 35°C

## 7.3. Specific end use(s)

see section 1.2

## **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters



according to UK REACH Regulation

# MIT700RE, Comp. B

Revision date: 29.11.2022

Page 5 of 13

## **DNEL/DMEL** values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
25513-64-8	2,2,4(or 2,4,4)-Trimethylhexane-1,6-diam	ine		
Consumer DI	NEL, long-term	oral	systemic	0,05 mg/kg bw/day
1477-55-0	m-Phenylenebis(methylamine)			
Worker DNE	L, long-term	inhalation	systemic	1,2 mg/m <sup>3</sup>
Worker DNE	L, long-term	inhalation	local	0,2 mg/m³
Worker DNE	L, long-term	dermal	systemic	0,33 mg/kg bw/day
104-15-4	p-Toluenesulphonic acid			
Worker DNE	L, long-term	dermal	systemic	7,6 mg/kg bw/day
Worker DNE	L, long-term	inhalation	systemic	53,6 mg/m³
Consumer DI	NEL, long-term	dermal	systemic	2,5 mg/kg bw/day
Consumer DI	NEL, long-term	inhalation	systemic	8,7 mg/m³
Consumer DI	NEL, long-term	oral	systemic	0,05 mg/kg bw/day

# **PNEC** values

CAS No	Substance	
Environmer	ntal compartment	Value
25513-64-8	3 2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine	
Freshwater		0,102 mg/l
Marine wate	er	0,01 mg/l
Freshwater	sediment	0,662 mg/kg
Marine sedi	iment	0,062 mg/kg
Micro-orgar	nisms in sewage treatment plants (STP)	72 mg/l
1477-55-0	m-Phenylenebis(methylamine)	
Freshwater		0,094 mg/l
Marine wate	er	0,009 mg/l
Freshwater	sediment	0,43 mg/kg
Marine sedi	iment	0,043 mg/kg
Micro-orgar	nisms in sewage treatment plants (STP)	10 mg/l
Soil		0,045 mg/kg
90-72-2	2,4,6-Tris(dimethylaminomethyl)phenol	· · ·
Freshwater		0,084 mg/l
Marine wate	er	0,0084 mg/l
Micro-orgar	nisms in sewage treatment plants (STP)	0,2 mg/l
104-15-4	p-Toluenesulphonic acid	· ·
Freshwater		0,073 mg/l
Marine wate	er	0,0073 mg/l
Freshwater	sediment	0,0577 mg/kg
Marine sedi	iment	0,00577 mg/kg
Soil		0,016 mg/kg



according to UK REACH Regulation

# MIT700RE, Comp. B

Page 6 of 13

Revision date: 29.11.2022

## Additional advice on limit values

This mixture contains quartz (inorganic filler) which is firmly bound in the pasty component, and thus not freely available during use, so that a risk of dust inhalation is excluded. Exposure limit values for respirable dusts are not relevant for this product.

## 8.2. Exposure controls







#### Appropriate engineering controls

Provide adequate ventilation. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means.

## Individual protection measures, such as personal protective equipment

## Eye/face protection

Wear eye/face protection. Wear safety glasses.

## Hand protection

Recommended material: NBR (Nitrile rubber) Breakthrough time: > 480 min Thickness of the glove material: 0,7 mm DIN-/EN-Norms EN 374

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

#### **Skin protection**

Wear suitable protective clothing.

#### **Respiratory protection**

In case of inadequate ventilation wear respiratory protection. Respiratory protection with combination filter A1P2 (organic gases/vapors and particles) recommended.

## **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

	Physical state: Colour: Odour:	solid (pasty) grey / red characteristic		
	Odour threshold:	No data available		
	Changes in the physical state			
	Melting point/freezing point:		r	not determined
	Boiling point or initial boiling point and boiling range:		r	not determined
	Flash point:			not applicable
	Flammability Solid/liquid: Gas:		r	not determined not applicable
	Lower explosion limits:		r	not determined
	Upper explosion limits:		r	not determined
	Self-ignition temperature Solid:		r	not determined
<i>/</i> i	aion No: 1.26		1	



according to UK REACH Regulation

## MIT700RE, Comp. B

Page 7 of 13

Revision date: 29.11.2022	, <b>.</b>	
Gas:	not applicable	
Decomposition temperature:	not determined	
pH-Value:	not determined	
Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.	
Solubility in other solvents not determined		
Partition coefficient n-octanol/water:	not determined	
Vapour pressure:	not determined	
Density (at 20 °C):	1,42 g/cm³	
Relative vapour density:	not determined	
9.2. Other information		
Information with regard to physical has Oxidizing properties Not oxidising. Other safety characteristics	zard classes	
Solid content:	not determined	
Evaporation rate:	not determined	
SECTION 10: Stability and reactivity		
<ul> <li><u>10.1. Reactivity</u> see section 10.3</li> <li><u>10.2. Chemical stability</u> The product is stable under storage at <u>10.3. Possibility of hazardous reactions</u> Violent reaction with: Oxidising agent <u>10.4. Conditions to avoid</u> see section 7.2</li> <li><u>10.5. Incompatible materials</u> Oxidising agent, strong</li> <li><u>10.6. Hazardous decomposition products</u> No known hazardous decomposition products</li> </ul>	broducts.	

## 11.1. Information on hazard classes as defined in GB CLP Regulation

## Acute toxicity

Harmful if swallowed.

## **ATEmix calculated**

ATE (oral) 1051,3 mg/kg; ATE (inhalation vapour) 107,60 mg/l; ATE (inhalation dust/mist) 15,100 mg/l



according to UK REACH Regulation

# MIT700RE, Comp. B

Revision date: 29.11.2022

Page 8 of 13

CAS No	Chemical name	Chemical name				
	Exposure route	Dose		Species	Source	Method
25513-64-8	2,2,4(or 2,4,4)-Trimethy	ylhexane-1,	6-diamine			
	oral	ATE mg/kg	500			
1477-55-0	m-Phenylenebis(methy	lamine)				
	oral	LD50 mg/kg	930	Rat		
	dermal	LD50 mg/kg	2000	Rabbit		
	inhalation (1 h) vapour	LC50	3,89 mg/l	Rat		
	inhalation dust/mist	ATE	1,5 mg/l			
90-72-2	2,4,6-Tris(dimethylamir	nomethyl)ph	nenol			
	oral	LD50 mg/kg	2169	Rat		
	dermal	LD50 mg/kg	1280	Rat		

#### Irritation and corrosivity

Causes severe skin burns and eye damage.

Causes serious eye damage.

#### Sensitising effects

May cause an allergic skin reaction. (2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine; m-Phenylenebis(methylamine))

## Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

#### STOT-single exposure

Based on available data, the classification criteria are not met.

#### **STOT-repeated exposure**

Based on available data, the classification criteria are not met.

## Aspiration hazard

Based on available data, the classification criteria are not met.

#### Further information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

## **SECTION 12: Ecological information**

#### 12.1. Toxicity

The product is not: Ecotoxic.



Page 9 of 13

## according to UK REACH Regulation

# MIT700RE, Comp. B

Revision date: 29.11.2022

CAS No	Chemical name							
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method	
25513-64-8	2,2,4(or 2,4,4)-Trimethy	lhexane-1,	6-diamine					
	Acute algae toxicity	ErC50 mg/l	43,5	72 h	Selenastrum capricornutum		OECD 201	
	Fish toxicity	NOEC mg/l	10,9	30 d	Danio rerio (zebrafish)		OECD 210	
	Crustacea toxicity	NOEC mg/l	1,02	21 d	Daphnia magna (Big water flea)		OECD 211	
1477-55-0	m-Phenylenebis(methylamine)							
	Acute fish toxicity	LC50 mg/l	87,6	96 h	Oryzias latipes (Ricefish)		OECD 203	
	Acute algae toxicity	ErC50 mg/l	32,1	72 h	Selenastrum capricornutum		OECD 201	
	Acute crustacea toxicity	EC50 mg/l	15,2	48 h	Daphnia magna (Big water flea)		OECD 202	
	Crustacea toxicity	NOEC	4,7 mg/l	21 d	Daphnia magna (Big water flea)		OECD 211	
90-72-2	2,4,6-Tris(dimethylamin	omethyl)pł	nenol					
	Acute fish toxicity	LC50	175 mg/l	96 h	Cyprinus carpio (Common Carp)			
	Acute algae toxicity	ErC50	84 mg/l	72 h	Desmodesmus subspicatus		OECD 201	
	Algae toxicity	NOEC mg/l	6,25	3 d				

## 12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
25513-64-8	2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine			
		7 %	28	

## 12.3. Bioaccumulative potential

The product has not been tested.

## Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
25513-64-8	2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine	-0,3
1477-55-0	m-Phenylenebis(methylamine)	0,18
90-72-2	2,4,6-Tris(dimethylaminomethyl)phenol	0,219
104-15-4	p-Toluenesulphonic acid	0,93

#### BCF

CAS No	Chemical name	BCF	Species	Source
1477-55-0	m-Phenylenebis(methylamine)	2,69		

## 12.4. Mobility in soil

The product has not been tested.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH. The product has not been tested.



according to UK REACH Regulation

# MIT700RE, Comp. B

Revision date: 29.11.2022

Page 10 of 13

## 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

## 12.7. Other adverse effects

No information available.

#### Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

## **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

#### **Disposal recommendations**

Subsequent waste code numbers of the European Waste Catalogue are considered as recommendations. Dispose of waste according to applicable legislation. Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

#### List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

#### List of Wastes Code - used product

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

#### List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

#### **SECTION 14: Transport information**

## Land transport (ADR/RID)

14.1. UN number or ID number:	UN 3259
14.2. UN proper shipping name:	AMINES, SOLID, CORROSIVE, N.O.S. (2,2,4(or 2,4,4)
	-Trimethylhexane-1,6-diamine; m-Phenylenebis(methylamine))
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8
	8
Classification code:	C8 <sup>~</sup>
Special Provisions:	274
Limited quantity:	1 kg
Excepted quantity:	E2
Transport category:	2
Hazard No:	80
Tunnel restriction code:	E



Revision date: 29.11.2022

# **Safety Data Sheet**

according to UK REACH Regulation

# MIT700RE, Comp. B

Page 11 of 13

Inland waterways transport (ADN) <u>14.1. UN number or ID number:</u> <u>14.2. UN proper shipping name:</u>	UN 3259 AMINES, SOLID, CORROSIVE, N.O.S. (2,2,4(or 2,4,4) -Trimethylhexane-1,6-diamine; m-Phenylenebis(methylamine))
<u>14.3. Transport hazard class(es):</u> <u>14.4. Packing group:</u> Hazard label:	8    8
Classification code:	C8 Č
Special Provisions:	274
Limited quantity:	1 kg
Excepted quantity:	E2
Marine transport (IMDG)	
14.1. UN number or ID number:	UN 3259
14.2. UN proper shipping name:	AMINES, SOLID, CORROSIVE, N.O.S. (2,2,4(or 2,4,4) -trimethylhexane-1,6-diamine; m-Phenylenebis(methylamine))
<u>14.3. Transport hazard class(es):</u>	8
14.4. Packing group:	Ш
Hazard label:	8
	8
Special Provisions:	274
Limited quantity:	1 kg
Excepted quantity: EmS:	E2
	F-A, S-B
Air transport (ICAO-TI/IATA-DGR) 14.1. UN number or ID number:	UN 3259
14.2. UN proper shipping name:	AMINES, SOLID, CORROSIVE, N.O.S. (2,2,4(or 2,4,4)
14.2. On proper snipping name.	-trimethylhexane-1,6-diamine; m-Phenylenebis(methylamine))
<u>14.3. Transport hazard class(es):</u>	8
14.4. Packing group:	П
Hazard label:	8
Special Provisions:	A3 Á803
Limited quantity Passenger:	5 kg
Passenger LQ:	Y844
Excepted quantity: IATA-packing instructions - Passenger:	E2 859
IATA-packing instructions - Passenger:	15 kg
IATA-packing instructions - Cargo:	863
IATA-max. quantity - Cargo:	50 kg
14.5. Environmental hazards	-
ENVIRONMENTALLY HAZARDOUS:	Νο
14.6. Special precautions for user	
No information available.	



according to UK REACH Regulation

## MIT700RE, Comp. B

Page 12 of 13

## Revision date: 29.11.2022

## 14.7. Maritime transport in bulk according to IMO instruments

not applicable

## **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulatory information

Restrictions on use (REACH, annex XVII): Entry 75 Information according to 2012/18/EU Not subject to 2012/18/EU (SEVESO III) (SEVESO III):

#### Additional information

VOC content: 21,7 % (DIN EN ISO 11890-2)

To follow: 850/2004/EC , 79/117/EEC , 689/2008/EC

#### National regulatory information

Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juvenile
	work protection guideline' (94/33/EC).
Water hazard class (D):	2 - obviously hazardous to water
Skin resorption/Sensitization:	Causes allergic hypersensitivity reactions.

#### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

## **SECTION 16: Other information**

#### Abbreviations and acronyms

ADN: Accord européen relativ au transport international des marchandises Dangereuses par voie de Navigation (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways) ADR: Accord européen sur le transport des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road) BCF: Bioconcentration factor CAS: Chemical Abstracts Service CLP: Classification, Labeling and Packaging DMEL: Derived Minimal Effect level **DNEL: Derived No Effect Level** EC50: Effective concentration, 50% IATA: International Air Transport Association IATA-DGR: Dangerous Goods Regulations (DRG) for the air transport (IATA) ICAO: International Civil Aviation Organization IC50: Inhibitory concentration, 50% IMDG: International Maritime Code for Dangerous Goods LC50: Lethal concentration, 50% LD50: Lethal dose, 50% NOEC: No Observed Effect Concentration OECD: Oragnisation for Economic Co-operation and Development PBT: persistent, bioaccumulative and toxic vPvB: very persistent and very bioaccumulative **PNEC: Predicted No Effect Concentration** REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals RID: Règlement concernant le transport international ferroviaire de marchandises dangereuses (Regulations Concerning the International Carriage of Dangerous Goods by Rail) VOC: Volatile organic compound



according to UK REACH Regulation

# MIT700RE, Comp. B

Revision date: 29.11.2022

Page 13 of 13

Acute Tox. 4: Acute toxicity, Category 4 Aquatic Chronic 3: Long-term aquatic hazard, Category 3 Eye Dam. 1: Serious eye damage/eye irritation, Category 1 Eye Irrit. 2: Serious eye damage/eye irritation, Category 2 Skin Corr. 1B: Skin corrosion/irritation, Category 1B Skin Irrit. 2: Serious eye damage/eye irritation, Category 2 Skin Sens. 1: Skin sensitilization, Category 1

## Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Acute Tox. 4; H302	Calculation method
Skin Corr. 1A; H314	Calculation method
Eye Dam. 1; H318	Calculation method
Skin Sens. 1; H317	Calculation method

#### Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
LI/12	Harmful to aquistic life with long lasting effects

## H412 Harmful to aquatic life with long lasting effects.

#### Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)